

Models:

☐ BS-CX

☐ BS-RX

Infra-Red Salamander Broiler

☐ BS-WX

☐ BS-RX-48

Item:	
Quantity:	
Project:	
Approval:	
Date:	

		US. Range
		_
10.0		

Model BS-CX

Standard Features:

☐ BS-RX-60

- Stainless steel front, sides, and top
- Single, 30,000 atomospheric infra-red burner designed for heavy broiling
- Available in Natural or Propane gas
- 5 position, positive lock, adjustable rack height
- Large capacity removable grease pan
- Designed to be installed on a counter, wall or range mounted on Cuisine and Performer Series ranges

Broiling grid 28" (711mm)
Wide x 13 1/2" (343mm)
Deep

☐ BS-RX-72

- Heavy-duty, spring assisted carriage is angle iron construction for long life and durability
- 1/2" NPT top gas inlet
- One Year limited parts and labor warranty (USA and Canada only)

Optional Features:

- Interconnection gas pipe for range mounting
- S/S bottom available for BS-RX Range mount models and BS-WX wall mount.

Specification:

Unit shall be a U.S. Range Infrared Salamander Broiler, Model ______. Single 30,000 BTU atmospheric infra-red burner, with 5 position adjustable rack. Stainless steel finish on front, sides, and top, available in natural or propane gas. Unit to be range, (BS-RX), counter, (BS-CX), or wall mounted, (BS-WX).










Model #	Description
BS-CX	36" wide Salamander Broiler for countertop use (with 4" (102mm) legs)
BS-WX	36" wide Salamander Broiler for wall mounting (with mounting brackets)
BS-RX	36" Salmander Broiler for range mounting (with backguard)
BS-RX-48	36" Salmander Broiler to mount on 48" range W/12" (305mm) High Shelf
BS-RX-60	36" Salmander Broiler to mount on 60" range W/24" (610mm) High Shelf
BS-RX-72	36" Salamander Broiler to mount on 72" range W/36" (914mm) High Shelf


Many local codes exist and it is the responsibility of the owner and installer to comply with those codes.


Garland/U.S. Range products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland / U.S. Range will not provide service, warranty, maintenance or support of any kind other than in commercial applications.

Model #	Weight Lbs/Kg	Cu Ft
BS-RX	205/93	28
BS-CX	210/95	20
BS-WX	192/87	20
BS-RX-48	230/105	30
BS-RX-60	260/118	40
BS-RX-72	280/127	48



Manifold Operating Pressure				
Natural Gas	5.0" WC (12.5mbar)			
Propane	11.0" WC (28mbar)			





Form# BSX (06/07)